

# Landline™ 8

ON-SURFACE TURBONET™ FLOW

## Applications

- On-surface installation
- Shrubs, flower beds and vegetable gardens
- Narrow planting areas
- Short laterals length
- Large pots and containers

## Specifications

- Dripper flow rates:  
2.0 l/h (nominal flow rate at 1.0 bar pressure)
- Uses Landline 8 mm fittings
- Maximum operation pressure: 2 bar
- Recommended filtration: 120 mesh
- Dripperline OD (outside diameter):  
8.0 mm
- Dripperline ID (inside diameter):  
6.4 mm

## Features and Advantages

- Large, efficient TurboNet™ flow path
- Easy installation
- Tubing flexibility adapts to any shape of planting area
- UV-resistant dripperline
- Labor saving on-surface installation
- Long lasting reliability and durability



**Landline™ 8 • O.D. 8.0 mm • Inlet pressure: 1.0 bar • Max. lateral length\* (m) / spacing between drippers (m)**

Flow rate (l/h)	0.3	0.4	0.5
2.0	15	18	22

\*Minimum pressure considered = 0.5 bar , calculated in a plain area

For maximal length at other inlet pressures, please contact your Netafim distributor or representative. Other spacings can be supplied on request.

Product	O.D. (mm)	Wall thickness (mm)	Flow rate (l/h)	Spacing (m)	Color	Coil length (m)
Landline™ 8	8	0.8	2.0	0.3	brown	25
				0.4	dark brown	50
				0.5		100
						200

One data from each column is required to achieve a complete catalog description, e.g. Landline™ , 8 mm, 0.8 mm, 2.0 l/h, 0.5 m, brown, 200 m coil.

	<b>Stabilizer</b> 8 mm 32000-002150
	<b>Barbed/start coupling</b> 8 mm 32500-002000
	<b>Barbed elbow</b> 8 mm 32500-001900
	<b>Barbed T</b> 8 mm 32500-002100