

## Diameter and wall thickness - Hydrolite Tape



Revised 6/2002

Product	I.D. (mm)			W.T.		
	Min	Nominal	Max	Min (mm)	Nominal (mm)	Nominal (MIL)
<b>16/8</b>	15.9	<b>16</b>	16.1	0.18	<b>0.2</b>	<b>8</b>
<b>16/10</b>	15.9	<b>16</b>	16.1	0.23	<b>0.25</b>	<b>10</b>
<b>16/12</b>	15.9	<b>16</b>	16.1	0.27	<b>0.3</b>	<b>12</b>

# Hydrolite Specifications



Revised 03/2003

No.	Dripline	Color	Flow rate l/h	W.T. MIL	I.D. mm	No D mm	MAX PRE M
1	16/8/0.6/015	Black	0.63	8	16	16	1.2
2	16/8/1/015	Brown	0.98	8	16	16	1.2

# Hydrolite - Flow Rate Vs. Pressure



Revised 03/2003

Pressure ( m )	Flow Rate Per Dripper	
	16/8/1/015 ( l/h )	16/8/0.6/015 ( l/h )
6	0.78	0.48
7	0.84	0.53
8	0.89	0.56
9	0.94	0.59
<b>10</b>	<b>0.98</b>	<b>0.63</b>
11	1.02	0.66
12	1.06	0.69

Pressure ( p.s.i )	Flow Rate Per Dripper	
	16/8/1/015 U.S.gph	16/8/0.6/015 U.S.gph
8.70	0.21	0.13
10.15	0.22	0.14
11.60	0.24	0.15
13.05	0.25	0.16
<b>14.50</b>	<b>0.26</b>	<b>0.17</b>
15.95	0.27	0.18
17.40	0.28	0.18