

TRAILCO T100

Capable of watering an area 165m long and 52m wide per run with no further attention.


Hose Size: 67m of 38mm (11/2 inch)

SPRINKLER		Sprinkler Pressure *		· ·		Wetted Width		Full Circle Precipitation Rate (avg.)		area per		Gross Application (9m/hr) 13 Hour Run		loss	
	*														
	kPa	PSI	l.p.s	GPM	m	ft.	mmph	p.p.h	ha	Ac	mm	ins	kPa	PSI	
Nelson F80V 11/32" Nozzle Plus Rotating Sprinkler Arm Jets	345	50	1.96	25.9	44	144	5.1	20	0.34	0.85	27.5	1.08	42	6.1	
	414	60	2.14	28.2	46	152	5.1	20	0.36	0.89	28.4	1.12	49	7.1	
	483	70	2.30	30.4	49	160	4.8	19	0.38	0.94	29.0	1.14	56	8.1	
Nelson F80V 3/8" Nozzle Plus Rotating Sprinkler Arm Jets	345	50	2.24	29.6	46	150	5.6	22	0.36	0.88	30.2	1.19	54	7.8	
	414	60	2.46	32.5	48	158	5.3	21	0.38	0.93	31.4	1.24	63	9.1	
	483	70	2.63	34.7	51	166	5.3	21	0.39	0.98	32.0	1.26	72	10	
Nelson F80V 13/32" Nozzle Plus Rotating Sprinkler Arm Jets	345	50	2.56	33.8	48	156	5.8	23	0.37	0.92	33.1	1.30	69	10	
	414	60	2.81	37.1	51	166	5.6	22	0.39	0.98	34.2	1.35	82	12	
	483	70	3.02	39.9	52	172	5.6	22	0.41	1.01	35.4	1.40	93	13	
Nelson F80V 7/16" Nozzle Plus Rotating Sprinkler Arm Jets	345	50	2.86	37.7	49	162	6.1	24	0.39	0.95	35.6	1.40	84	12	
	414	60	3.16	41.7	52	172	5.8	23	0.41	1.01	37.1	1.46	101	15	
	483	70	3.40	44.9	55	180	5.8	23	0.43	1.06	38.1	1.50	116	17	

NOTE:- APPROXIMATE LANE SPACINGS CALCULATED USING 0.65 WIND FACTOR, (65%OF THE WETTED WIDTH/SPRINKLER DIAMETER)

* Sprinkler performance is based on the manufacturers data which has been obtained under ideal test conditions and may be adversely affected by wind or other factors.

Trailco Irrigation makes no representation regarding droplet condition, uniformity or application rate.



Hose Size: 38mm (1½") x 67 metres (220') Hose **Cable Length:** 120 metres (394')

FEATURES:

- Drive Unit Powered by rotating sprinkler arms through a gear train and worm drive to cable drum. Simple and efficient.
- Travel Speed Adjustment A simple operation by varying the angle of the rotating sprinkler arm jets and available pressure.
- Automatic Shut-off The water supply at the sprinkler is automatically shut off at end of run.
- Longer Life Gears are made of gunmetal and the chassis is hot dip galvanised.
- Cable Rewind Handle For easy cable retrieval on an aborted run.
- Hose Reel For storage of hose when not being used and for shifting from one area to another.

- Hose Guide Arm To guide the hose onto the reel when retrieving the hose.
- All brass sprinkler and range of nozzle sizes.
- Cable anchor stake supplied with Traveller as standard.
- Cover protecting drive mechanism.
- Sliding Handle/Drawbar allows easy repositioning of Traveller.
- Easy to service.

OPTIONAL EXTRAS:

• Front Axle Kit - Wheels lift the front skid off the ground, allowing easier travel, with less impact on the turf.

Ideally suited for watering: Golf Courses Sportsfields, Gardens, Parks, Estates, Turf areas, Race Courses, Turf Farms, Small Crops and for Dust Control.


TRAILCO IRRIGATION (AUST.)

1289 KINGSFORD SMITH DRIVE PINKENBA QLD. 4008

Phone (07) 3260 1828 Fax (07) 3260 1877 International Callers: Country (61) Area (7) www.trailco.com.au sales@trailco.com.au



SHIPPING DIMENSIONS



SOLD AND SERVICED BY: